| ARCHITECTURA | | PANEL CUBICLES |
|---------------------------|--|---------------------------------------|
| PRODUCT DATA | SHEET | |
| TOILETS | | K32/120/01 |
| PREFFERED SU | PPLIER INFORMATION | |
| NBS REFERENCE K | 32 | |
| MANUFACTURER: | | |
| VENESTA WASHRO | OMS LTD | |
| Chartwell Court, West M | ill | |
| Imperial Business Park | | |
| Gravesend, Kent, DA11 | ODL | |
| Tel : 01474 353333 | Fax: 01474 533558 | |
| Website: www.venesta. | co.uk | |
| Supplier Contact: Luke | Rodwell (Specification Manager) <u>luke.rodwell@venesta.co.uk</u> | |
| PRODUCT DESC | RIPTION | |
| ICL APPROVED SPE | CIFICATION | |
| Range: | Unity SGL | |
| Description: | Simple & striking. This clean modern design is the UK's | most ecomnomical, well designed flush |
| | cubicle range. Whatever the environment, Unity's 'floating' flush front always males an impact | |
| Application: | All areas. High end appeal. High volume traffic. | |
| Material: | 13mm Solid Grade Laminate (SGL) & Stainless Steel Fittings | |
| Size: | To suit application. | |
| Environmental: | Meet with the formaldehyde E1 emission level. | |
| Recycling: | Standard fittings can be recycled at specialist licensed centres | |
| Warranty: | 10 year warranty - refer to maintenance document for details | |
| Production: | Manufactured in the UK | |

TYPICAL NBS SPECIFICATION

| NBS: K32/120/01 PANEL CUBI | CLES - UNFRAMED | | |
|---|---|--|--|
| Standard: | Approved panel cubicles to Imperial College London architectural standards. | | |
| Manufacturer: | Venesta Washrooms Ltd | | |
| Range: | Unity SGL | | |
| 2120mm standard height upto | 2600mm full height from FFL including 50mm floor clearance | | |
| Overall depth: 2000mm maxim | um recommended from face of back wall or rear ducting | | |
| Panels/Doors: 13mm Solid Gra | de Laminate (SGL) | | |
| Edge treatment: All edges radi | used and polished (black) | | |
| Hinges: Spring loaded stainless steel butt hinges | | | |
| Colour/Finish: From Venesta's standard colour range | | | |
| Headrail: Slimline aluminium channel profile with stainless steel finish allowing cubicles to finish 20mm below | | | |
| ceiling height | | | |
| Pedestals: Stainless steel with brushed finish. | | | |
| Indicator bolt and keep: Stainless steel, with brushed finish, lever operated bolt with circular face plate and | | | |
| emergency release facility | | | |
| Wall and partition to pilaster fixings: Through fix brushed finish stainless steel angle cleats | | | |