

Imperial College London

ARCHITECTURAL STANDARDS PRODUCT DATA SHEET

M12 RESIN FLOOR FINISHES

RESIN FLOOR FINISHES

M12/110

NBS Create:20-55-77/170

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M12.

MANUFACTURER:

ALTRO LTD

Works Road, Letchworth Garden City

Hertfordshire, SG6 1NW

Tel: 01462 707600

E-mail: enquiries@altro.com

Website: <http://www.altro.co.uk>

Supplier Contact: Altro Customer Care Centre enquiries@altro.com



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Altro Screed 5mm Rapicure slip resistant

Slip Resistance: PTV \geq 40

Description: Solvent-free epoxy resin

FeRFA type: 6

Application: Areas of use: for areas where there is an increased risk of slipping and a quicker return to service is required. Typical areas include canteens, laundries, CDT, custodial areas, changing rooms, food and drink packing areas

Wear Characteristics: Medium—heavy Duty

Nominal Thickness: 5mm

Service Temperature: 0 to 60C

Chemical Resistance: Moderate

Guarantee: 10 year product guarantee.

Life Expectancy: 15 years

Cleaning Method: Scrubber Dryer

TYPICAL NBS SPECIFICATION

M12: 110 RESIN FLOORING

Standard: Approved Resin Flooring to Imperial College London Architectural Standards

Location: To architects finishes schedules.

Base: As per architects details., Typically sand/cement modified screed, concrete, timber or metal

Priming: Refer to product data sheet for correct primer—dependant on substrate

Manufacturer: Altro Ltd, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW

Range: Altro Screed

Type: Solvent-free epoxy resin

Colour: All colours approved.

Moisture Content: Substrate moisture content should not exceed 75% R.H. or 5% moisture content by weight.

Joints: All vertical joints to be transferred through the cove detail and in-filled with Altro Expand vertical.

For full NBS specification contact Altro