


ARCHITECTURAL STANDARDS	FLOOR FINISHES
PRODUCT DATA SHEET	
N13: SANITARYWARE	N13/300

<p>PREFERRED SUPPLIER INFORMATION</p> <p>NBS REFERENCE N13/300</p> <p>MANUFACTURER:</p> <p>IDEAL STANDARD (UK) LTD</p> <p>Address The Bathroom Works, National Avenue Kingston upon Hull HU5 4HS</p> <p>Tel 0870 122 8282</p> <p>E-mail info@idealspec.co.uk</p> <p>Website: www.idealspec.co.uk</p> <p>Contact:</p>	
---	---

<p>PRODUCT DESCRIPTION</p> <p>ICL APPROVED SPECIFICATION</p> <p>Range: Sandringham 21</p> <p>Type: Back to wall WC with horizontal outlet</p> <p>Use Suitable for commercial and domestic use</p> <p>Material Vitreous china to BS 3402, BS EN 997 and BS EN 33</p> <p>Cistern Concealed</p> <p>Recyclable: Yes</p> <p>Warranty: Lifetime against manufacturing or material defect</p> <p>Production: Made in the UK</p>
--

TYPICAL NBS SPECIFICATION	
N13:300	WC'S AND CISTERNS
Standard:	Approved WC Pan/Cistern to Imperial College London Architectural Standards, BS3403, BS EN 997 and BS EN 33
Type:	Short projection, wall mounted WC pan with wash down action and box flushing rim
PAN	
Product reference:	E8974-Sandringham 21 Back to Wall WC Suite - Sandringham 21 Back to Wall WC Pan
Material	Vitreous china to BS 3402, BS EN 997 and BS EN 33
SEAT & COVER	S2985-WC Seat - Sandringham 21 Seat & Cover, slow close E1316- Seat and Cover Sandringham 21 Metal Hinges
Manufacturer:	Ideal Standard (UK) Ltd, National Avenue, Kingston upon Hull HU5 4HS
Material	Plastic
Finish & Colour	White
WC CONNECTOR	
	WC Outlet Connector S4300- WC Outlet Connector- Panekta Finned Conversion Bend 90 Degree E3222- WC Outlet Connector- Panekta Finned Connector 14 Degree
Cistern	Capacity: 4.5 litres •Secondary Capacity: 3.0 litre • Material: Plastic • Weight:3.00 kg
	or turned P trap
Manufacturer:	Ideal Standard (UK) Ltd, National Avenue, Kingston upon Hull HU5 4HS
Colour	White

BRACKETS:	E0060 pair of support brackets for for load bearing walls up to 150mm thick and 145mm long to suit partitions 13-25mm thick
ACCESSORIES:	Support brackets screwed to floor within the duct. WC to be fixed to support brackets with bolts supplied and bolts screwed to back wall with brackets
Jointing	Joint between WC pan and panel to be sealed with waterproof silicon sealant, colour White
Alternative Frame	Suitable for all Ideal Standard In Wall WC frames