

**ARCHITECTURAL STANDARDS  
PRODUCT DATA SHEET**

Painting

M60 /Painting / Clear Finishing

M60 / 160

**PREFERRED SUPPLIER INFORMATION**

NBS REFERENCE M60 / 130

MANUFACTURER:

**Crown Trade , Crown Trade Paints Ltd**

Address

Crown House - Hollins Road, Darwen, Lancasher BB30BG

Tel 0044 (0) 3332227070

E-mail

Website: [www.crownpaintspec.co.uk](http://www.crownpaintspec.co.uk)

Supplier: Contact: [info@crownpaintspec.co.uk](mailto:info@crownpaintspec.co.uk)



**PRODUCT DESCRIPTION**

ICL APPROVED SPECIFICATION

**Range:** Woodstain

**Description:** a durable woostain for all exterior softwood and hardwood joinery.

**Application:** Particularly suitable for doors & window frames

**Other**

Finish : Semi-gloss

Drying time: recoatable after 16-24 hours under normal drying conditions

Coverage: up to 15 sqm/litre in smooth surfaces

Wet film thickness: 66 micrometres at 15 sqm /l and Dry film thickness: 29 micrometres at 15 sqm/l

This product will remain usable for up to two years if stired correctly and remains un-opened

**TYPICAL NBS SPECIFICATION**

**M60 Painting / Clear Finishing - 160 Decorative woodstain varishing preservative**

**This product is associated with the following NBS clauses: M60 Painting/ Clear finishing - 160 Decoratibe woodstain preservative**

**This product is associated with the following NBSCreate clause: 45 - 35 - 84/ 418 Wood stains or dyes**